



SUREBOND

TECHNICAL DATA SHEET

SureStrip

Fast Acting Sealer Stripper

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

SUITABLE SUBSTRATES

Hardscape surfaces like pavers, concrete flat work and retaining walls, etc. Can also be used on manufactured and natural stone, concrete block, clay pavers and wet cast products both horizontal and vertical applications. Not for use on asphalt.

PRODUCT DESCRIPTION

SureStrip is a technologically advanced sealer stripper that has a wide range of applications. **SureStrip** is designed for the removal of acrylics, acrylic latex, polyurethane and other resin coatings and sealers from virtually any type of hardscape surface with minimal or no brushing. **SureStrip** can also be used as a spot cleaner to remove paint spots.

SureStrip's unique Clean Rinse Technology allows residue to be quickly and easily rinsed away with a high or low pressure washer. Protect plant materials from overspray and contact.

SureStrip is the sealer stripper of choice by contractors for both routine maintenance and restoration. It can be used to prepare your surface for sealing in tandem with S.R.B. (Stain & Rust Buster) for spot stain cleaning, Efflo Off for removal of efflorescence, SureClean for general purpose cleaning and Oil Extractor for oil stain removal. It is suitable for both horizontal and vertical surfaces.

Features	Benefits
What makes SureStrip different?	
Easy to Use	• Scrub free
User Friendly	• Non hazardous, non flammable and will not burn skin
Fast Acting	• Works in minutes
Strips Variety of Sealers/Coatings	• Wide range of application
Easy to Rinse	• Clean Rinse Technology
Safe	• Will not damage any hardscape substrate as well as wood, glass, metal, aluminum trim & masonry surfaces

SURFACE & AIR TEMPERATURES

Excessively high or low temperatures will produce poor results. Best cleaning results are obtained when air and surface temperatures are 40° F or above. Do not clean when temperatures are below freezing or will be overnight. If freezing conditions exist, allow adequate time for surface to thaw. If air temperatures exceed 90° F, flash cool the surface with water before applying product. Do not allow product to dry on a hot surface. Always rinse thoroughly while still wet.



PREPARATION / PRE-TESTING

Sweep and remove all loose soil and debris from the surface. Protect adjacent and surrounding surfaces not intended to be stripped. Cover foliage with polyethylene or other proven protective material. Prior to stripping, test stripper on a small, inconspicuous area to determine the suitability of this product for a specific sealer and surface. Testing should confirm effectiveness of stripper and desired surface dwell time on each type of surface and sealer designated to be removed. Allow test areas to dry thoroughly before evaluating final appearance and results.

DILUTION

SureStrip is a concentrated sealer stripper that is ready for use. No dilution is necessary.

APPLICATION INSTRUCTIONS

Apply **SureStrip** using a low-pressure sprayer such as a garden sprayer or it can be brushed, wiped, or rolled onto the surface. Depending on the sealer or coating, more than one application may be needed. If surface is sloped apply **SureStrip** from the top down using a side-to-side motion. Allow **SureStrip** to dwell for at least five to ten minutes before doing a scratch test. Scratch at the sealer or coating with a sharp object to see if the substrate is visible. If the substrate is visible where tested then it is ready to be rinsed. Improve results by scrubbing surface with a natural fiber brush to agitate and loosen sealer. If the substrate is not visible or if the coating is gummy but not released, re-apply and let dwell for an additional ten minutes before re-testing. Rinse surface thoroughly with a cold water pressure washer with a wide tip no less than 25 to 40 degrees or a garden hose with nozzle. Only use as much pressure as needed to thoroughly clean as excessive high pressures can damage substrates. It may be necessary to do a secondary cleaning to remove old, heavier sealers. Do not allow product to dry on the surface. Always rinse-off thoroughly while wet.



SUREBOND

TECHNICAL DATA SHEET

SureStrip

Sealer Stripper

★ CONTRACTOR GRADE FOR RESIDENTIAL AND COMMERCIAL PROJECTS ★

COVERAGE RATES

Coverage rates will vary from 125 - 250 sq. ft. per gallon depending on the surface porosity, texture and age of sealer. Coverage based on single treatment. Some applications may require additional treatments. Additionally, actual coverage may vary depending on application method and other local conditions.

PACKAGING/SIZES

1 gallon containers

5 gallon pails

CONTAINER HANDLING/STORAGE

Store in a cool, dry place away from acids and protect from freezing. Keep container tightly closed when not in use. Do not use pressure to empty container. Wash thoroughly after handling. Do not use container as dilution or rinsing vessel. Empty containers retain residue and must be handled as if full.

SHELF LIFE

Two years when properly stored.

SAFETY INFORMATION

Precautionary Measures: Always wear goggles and rubber gloves when handling this product. Keep off of skin and clothing. If material comes in contact with clothing, wash before reuse.

SureStrip contains hydrocarbon blend naphtha. Do not get in eyes, on skin or clothing. Avoid breathing fumes. Keep container closed when not in use. Use with adequate ventilation. Applicators should wear rubber boots, gloves, face shields and/or goggles to avoid splash to bare skin and eyes. Applicators should wear a rain suit (plastic, rubber or PVC), boots, gloves, face shields and/or goggles to avoid splash to bare skin and eyes. Though the potential for fuming of **SureStrip** is minimal, take precautions to avoid exposing building occupants to fumes. Dispose of empty containers according to federal, state and local requirements. Do not dilute **SureStrip**. Do not use for any other applications other than specified. Do not remove label. Read Material Safety Data Sheet for additional safety and health hazard information prior to use.

INSTRUCTIONS IN CASE OF CONTACT OR EXPOSURE

Eyes: Flood with water for fifteen minutes. Seek immediate medical attention. Remove contact lenses immediately.

Skin: Wash off with soap & water. Remove contaminated clothing.

Inhalation: Move to fresh air. If breathing is difficult, give oxygen and call a physician.

Ingestion: Drink large amounts of water to dilute. Do not induce vomiting. Seek immediate medical attention.

WARRANTY

Manufacturer warrants its products conform to the published specifications. No other warranties are expressed or implied, including those of merchantability or fitness or any purpose not expressly set forth herein. The user must determine suitability of the products for their particular use. Manufacturer and any seller's liability for incidental or consequential damage hereunder shall not exceed the purchase price of the product used.

ASSISTANCE & ADDITIONAL INFORMATION

For sales, specification assistance, technical questions, detailing, etc., please contact:



SEK

SUREBOND

3925 Stern Ave. • St. Charles, IL 60174

Email: info@sek.us.com

Fax: 630-762-0607

800-932-3343 | www.sek.us.com